

GOLD EAGLE



МЕРКОЛ

01.12.2015 . .

| | | | ml / g | . | 1 / . |
|-----|-----------|-------------------------------|----------|----|----------|
| 1. | 15210 | DIESEL POWER - 132 | 355 ml | 6 | 15.96 |
| 2. | 15211 | DIESEL POWER - 132 5-10 | 355 ml | 6 | 15.45 |
| 3. | 15212 | DIESEL POWER - 132 | 355 ml | 6 | 15.45 |
| 4. | 15223 | DIESEL POWER - 565 | 591 ml | 6 | 28.23 |
| 5. | 15224 | DIESEL POWER - 565 5-10 | 591 ml | 6 | 29.58 |
| 6. | 15225 | DIESEL POWER - 565 | 591 ml | 6 | 28.80 |
| 7. | 15229 | DIESEL POWER - 1:1500 | 3,785 l | 4 | 180.60 |
| 8. | 1637 | | 2x355 ml | 12 | 51.60 |
| 9. | 20301 | NO LEAK - | 473 ml | 6 | 19.90 |
| 10. | 20401 | NO LEAK - | 473 ml | 6 | 19.90 |
| 11. | 20601 | NO LEAK - | 473 ml | 6 | 19.90 |
| 12. | 21001 | Gold Eagle - | 887 ml | 12 | 14.91 |
| 13. | 21201 | Gold Eagle - | 236 ml | 12 | 10.83 |
| 14. | 21204 | Gold Eagle - 1 | 355 ml | 12 | 9.98 |
| 15. | 21402 | Gold Eagle - | 443 ml | 12 | 12.99 |
| 16. | 22204 | STA-BIL - 38 | 118 ml | 12 | 12.50 |
| 17. | 22239 | STA-BIL - 150 | 236 ml | 12 | 27.52 |
| 18. | 3020 | | 360 ml | 12 | 11.76 |
| 19. | ASD 24/2 | Alumaseal - 20 g | 20 g | 24 | 6.26 |
| 20. | ASBP24/12 | Alumaseal - 20g | 20g | 24 | 6.26 |
| 21. | ASLC16 | Alumaseal - 473 ml | 473 ml | 12 | 11.37 |
| 22. | AR12P | | 355 ml | 12 | 10.90 |

| | | | | | |
|-----|--|------------------------------|-------------------------------|--------------|-------------------------|
| 23. | CS 10 P | Gold Eagle - - 21 | 355 ml | 12 | 8.95 |
| 24. | DI55*** | Gold Eagle - - 1 . 2000 . | 1-10 . 11-50 . 51-208 . | 1 1 1 | 26.60 22.90 21.50 |
| 25. | GC-15 | Gold Eagle - | 354 g | 12 | 11.06 |
| 26. | HA51420 | CLINDO - | 539 g | 12 | 9.96 |
| 27. | HA54740 | HEET - 60 . | 355 ml | 12 | 11.09 |
| 28. | 28202 | HEET - - | 335 ml | 24 | 11.72 |
| 29. | RF 12P | Gold Eagle - | 355 ml | 12 | 8.85 |
| 30. | SA 16-12 | HEET - | 286g | 12 | 9.83 |
| 31. | MK-DI | - 500 . , | 250 ml | 12 | 15,50 |
| 32. | MK-HL | - | 295 ml | 6 | 45.00 |
| 33. | -AS/0.5 | - - | 500 ml | - | 5.60 |
| 34. | -IG/0.2 | - | 200 ml | - | 5.60 |
| 35. | MK-AN*** | - -60°C - | 1 kg 5 kg ** | 15 1 1 | 5.50 22.50 3.54 |
| 36. | MK-AN72/1 MK-AN72/5 | - LONG LIFE -72°C - | 1 kg 5 kg | 15 1 | 8.35 36.75 |
| 37. | MK-W1 *** MK-W5PET*** MK-W1000*** | - -40°C | 1 . 5 .PET ** | 15 1 1 | 2.95 14 2.65 |
| 38. | MK-W1/25*** MK-W5PET/25*** | - , -25°C | 1 . 5 . PE | 15 1 | 2.36 11.25 |
| 39. | MK-S1-1/2 | - , 1:2 | 1 . | 15 | 2.86 |
| 40. | MK-S3 | - . . | 3 . | 1 | 3.02 |
| 41. | MK-S5 | - . . | 5 . | 1 | 3.54 |
| 42. | MK-S1 MK-S1/5 | - , 1:5 | 1 . 5 . PE | 15 1 | 3,36 8.65 |
| 43. | -NO _x 10*** -NO _x 1000*** | - | 10 . ** | 1 1 | 0.96 0.72 |

- :
- -
 -
 - (*)
 - ** 200 1000 .
 - 50 . 200 ., 200 . 1000 .,
 - *** 24, 35, 37 () 43

“ e ”

.: 02/ 931 10 75, : 02/ 931 04 41
e-mail: office@merkury-bg.biz , www.merkury-bg.biz